



Łącznik pomocniczy, do PLS, PLZ, PKNM, ZP-A40...-ASA...IHK...WHK, Z-MS, 1W, 0.5JC

Typ
Catalog No. **ZP-WHK**
 286053

Program dostaw

Funkcja podstawowa			Akcesoria do zespolonego wyłącznika różnicowoprądowego FI/LS Akcesoria do wyłącznika ochronnego
Funkcja podstawowa – akcesoria			Łącznik pomocniczy
Aplikacja			Aparaty łączeniowe do zastosowań w przemyśle i budynkach funkcjonalnych
Asortyment			Akcesoria
Side mounting			for fitting on left to: LS, FI/LS
Diagram łączenia			

Świadectwo typu zgodnie z IEC/EN 61439

Dane techniczne dla zaświadczenia rodzaju konstrukcji			
Robocza temperatura otoczenia min.	°C	-5	
Robocza temperatura otoczenia maks.	°C	40	

Dane techniczne zgodne z ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary contact unit for distribution board (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss8.1-27-14-35-02 [AKE327010])			
Device fitting			Universal
Additional equipment			Auxiliary switch
Attached at delivery			No
Assembly width (TE)			0.5
Number of normally open contacts			0
Number of normally closed contacts			0
Number of change-over contacts			1
Number of fault-signal switches			0
Rated switch current	A	3	
Nominal rated voltage	V	230	
Control voltage type		AC	
With autotest for earth leakage function		No	
Suitable for max. number of poles main contact unit (total)		1	
Suitable for max. current main contact unit	A	6	

